



Supplemental Bid Bulletin No. 105150-1
 November 24, 2020

PROCUREMENT OF SERVICE VEHICLE FOR THE USE OF NAVOTAS INSTITUTE

This Supplemental Bid Bulletin No. 105150-1 is issued to modify or amend the Bid Documents. This shall form an integral part of the Bid Documents.

REFERENCE	AMENDMENT/CHANGE/CLARIFICATION
<p><u>SECTION VI. SCHEDULE OF REQUIREMENTS</u></p> <p><u>Description</u></p> <p>Purchase of service vehicle with LTO registration and stickers for the use of Navotas Vocational Training & Assessment Institute (NVTAI)</p> <p><u>Specifications:</u></p> <ul style="list-style-type: none"> • Overall Length: 4,260 mm • Overall Width: 1,695 mm • Overall Height: 1,895 mm • Wheelbase: 2,350 mm • Ground Clearance: 195 mm • Maximum Gross Vehicle Weight: 2,345 kg • Curb Weight: 1,200 kg • Payload: 1,145 kg • Engine: 2.2 4N14 Euro 4 compliant • Maximum Power: 99 horsepower @ 3,500 rpm • Maximum Torque: 200 Nm @ 1,000 – 3,500 rpm • Fuel System: Electronic Common Rail Direct Injection • Fuel Tank: 55 liters • Front Suspension: Independent, double wishbone • Rear Suspension: Semi-elliptic Leaf Spring • Front Brakes: 10-inch ventilated disc • Front Brakes: 10-inch Leading and Trailing drums • Steering: Ball-and-Nut Gear Type, Power steering • Steering Wheel: 2-spoke polypropylene • Tires: 185R14C-8PR • Wheels: 14 x 5.0 J steel rims 	<p><u>SECTION VI. SCHEDULE OF REQUIREMENTS</u></p> <p><u>Description:</u></p> <p>Purchase of service vehicle with LTO registration and stickers for the use of Navotas Vocational Training & Assessment Institute (NVTAI)</p> <p><u>Specifications:</u></p> <ul style="list-style-type: none"> • Overall Length: 4,260 mm • Overall Width: 1,695 mm • Overall Height: 1,895 mm • Wheelbase: 2,350 mm • Ground Clearance: 185 - 195 mm • Maximum Gross Vehicle Weight: 2,345 kg • Curb Weight: 1,200 kg • Payload: 1,145 kg • Engine: 2.2 – 2.5 Euro 4 compliant • Maximum Power: 99 horsepower @ 3,500 rpm • Maximum Torque: 200 Nm @ 1,000 – 3,500 rpm • Fuel System: Electronic Common Rail Direct Injection • Fuel Tank: 55 liters • Front Suspension: Independent, double wishbone • Rear Suspension: Semi-elliptic Leaf Spring • Front Brakes: 10-inch ventilated disc • Front Brakes: 10-inch Leading and Trailing drums • Steering: Ball-and-Nut Gear Type, Power steering • Steering Wheel: 2-spoke polypropylene • Tires: manufacturer • Wheels: manufacturer
<p><u>SECTION VII. TECHNICAL SPECIFICATIONS</u></p> <p><u>Specifications:</u></p> <p>Purchase of service vehicle with LTO registration and stickers for the use of Navotas Vocational Training & Assessment Institute (NVTAI)</p> <p><u>Specifications:</u></p> <ul style="list-style-type: none"> • Overall Length: 4,260 mm • Overall Width: 1,695 mm • Overall Height: 1,895 mm • Wheelbase: 2,350 mm • Ground Clearance: 195 mm • Maximum Gross Vehicle Weight: 2,345 kg • Curb Weight: 1,200 kg • Payload: 1,145 kg • Engine: 2.2 4N14 Euro 4 compliant 	<p><u>SECTION VII. TECHNICAL SPECIFICATIONS</u></p> <p><u>Specifications:</u></p> <p>Purchase of service vehicle with LTO registration and stickers for the use of Navotas Vocational Training & Assessment Institute (NVTAI)</p> <p><u>Specifications:</u></p> <ul style="list-style-type: none"> • Overall Length: 4,260 mm • Overall Width: 1,695 mm • Overall Height: 1,895 mm • Wheelbase: 2,350 mm • Ground Clearance: 185 - 195 mm • Maximum Gross Vehicle Weight: 2,345 kg • Curb Weight: 1,200 kg • Payload: 1,145 kg • Engine: 2.2 – 2.5 Euro 4 compliant



<ul style="list-style-type: none">• Maximum Power: 99 horsepower @ 3,500 rpm• Maximum Torque: 200 Nm @ 1,000 – 3,500 rpm• Fuel System: Electronic Common Rail Direct Injection• Fuel Tank: 55 liters• Front Suspension: Independent, double wishbone• Rear Suspension: Semi-elliptic Leaf Spring• Front Brakes: 10-inch ventilated disc• Front Brakes: 10-inch Leading and Trailing drums• Steering: Ball-and-Nut Gear Type, Power steering• Steering Wheel: 2-spoke polypropylene• Tires: 185R14C-8PR• Wheels: 14 x 5.0 J steel rims	<ul style="list-style-type: none">• Maximum Power: 99 horsepower @ 3,500 rpm• Maximum Torque: 200 Nm @ 1,000 – 3,500 rpm• Fuel System: Electronic Common Rail Direct Injection• Fuel Tank: 55 liters• Front Suspension: Independent, double wishbone• Rear Suspension: Semi-elliptic Leaf Spring• Front Brakes: 10-inch ventilated disc• Front Brakes: 10-inch Leading and Trailing drums• Steering: Ball-and-Nut Gear Type, Power steering• Steering Wheel: 2-spoke polypropylene• Tires: manufacturer• Wheels: manufacturer
--	--

For guidance and information of all concerned.

ATTY. JOEL JOSELITO DG. PARONG
BAC Chairperson



Republic of the Philippines
Metropolitan Manila
CITY OF NAVOTAS



**NAVOTAS VOCATIONAL TRAINING
AND ASSESSMENT (NAVOTAAS) INSTITUTE**

November 19, 2020

Atty. JOEL PARONG
Chairman
Bid and Awards Committee

Dear Atty. Parong:

This refers to the procurement of service vehicle amounting to P1,500,000.00 for the use of NavotaAs Institute. As discussed during the Pre-bid Conference yesterday, please be informed that the correct technical specifications provided are the following:

Query / Concern	Reply / Clarification
1. Ground Clearance: 195 mm	Ground Clearance: 185-195 mm
2. Engine: 2.2 4N14 Euro 4 compliant	Engine: 2.2 – 2.5 Euro 4 compliant
3. Tires: 185R14C-8PR	Tires: manufacturer
4. Wheels: 14 x 5.0 J steel rims	Wheels: manufacturer

For your appropriate action.

Thank you very much.

Very truly yours,


KATHRYN ANNE S. HILARIO
Officer-in-Charge

